



SINCE
1950

MALERVLIES

Nonwoven needle punched textile



Characteristic: Nonwoven textile mechanically bonded by needle punching and laminated by anti-slip transparent PE foil

Material content: 100 % Recycled fibres
PE foil, transparent, anti-slip, 20 - 25 g/m²
EVA binder

Colour: Multicolour

Weight: 200 to 300 g/m²

Standard width: 1 or 2 m

Funktion:



PROTECTION



SEPARATION



ANTI-SLIP

Use:



Material specification sheet

Date: 21.3.2023

Quality Management System ISO 9001, ISO 14001, ISO 45001 and ISO 50001



TRADITIONAL QUALITY NONWOVENS

Material specification sheet

Date: 21.3.2023

MALERVLIES

Nonwoven needle punched textile

MALERVLIES	230	250	270	300	
PHYSICAL PROPERTIES					
Weight [±10 %] / EN 29073-1	g/m ²	230	250	270	300
Thickness / DIN 53855-3	mm	1,4	1,6	1,7	1,8
FUNCTION					
ANTI-SLIP		X	X	X	X
Protection	P	X	X	X	X
CHARACTERISTICS					
Description	Nonwoven textile mechanically bonded by needle punching and laminated by transparent anti-slip PE foil				
Material content	Recycled fibres				
	PE foil, transparent, anti-slip, 20 - 25 g/m ²				
	EVA binder				
Colour	Various				
DIMENSION, PACKAGING AND STORAGE					
Roll width	m	1 or 2	1 or 2	1 or 2	1 or 2
Roll length	m	10, 25 or 50	25 or 50	25 or 50	25 or 50
Packaging	Rolls are packed in PE foil.				
Storage	In covered, clean and dry spaces				

The above technical parameters are average values and serve for general information. The manufacturer reserves the right to change it.