



SINCE  
**1950**

# TRADITIONAL QUALITY NONWOVENS

## VAFIX

Padding and Insulation fleece



- Characteristics:** Nonwovens textile bonded by stitching yarn, additional bothside sprayed by binder
- Material content:** 100 % PES staple fibers  
Stitching PES yarn
- Colour:** White
- Weight:** Od 100 do 300 g/m<sup>2</sup>
- Maximum width :** 90 - 180 cm
- Function:**



**Material Specification**

Date: 17. 3. 2023

Quality Management System ISO 9001, ISO 14001, ISO 45001 and ISO 50001



# TRADITIONAL QUALITY NONWOVENS

Material Specification

Date: 17. 3. 2023

## VAFIX

Padding and Insulation fleece

VAFIX	100	150	200	300	
<b>PHYSICAL PROPERTIES</b>					
Weight [ $\pm 10\%$ ] / ČSN EN 12 127	g/m <sup>2</sup>	100	150	200	300
<b>CONSTRUCTION</b>					
1. Density of posts [ $\pm 5\%$ ]	n / 10 cm	2,5	2,5	2,5	2,5
2. Density of posts [ $\pm 5\%$ ]	n / 10 cm	10	10	10	10
Row density [ $\pm 5\%$ ]	n / 10 cm	25 - 35	25 - 35	25 - 35	25 - 35
<b>SURFACE FINISH</b>					
Double-sided adhesive injection / density of posts 2,5		YES	YES	YES	YES
Double-sided adhesive injection / density of posts 10		NO	NO	NO	NO
<b>CHARACTERISTIC</b>					
Description		Nonwoven textile (fibrous layer) mechanically bonded by stitching yarn			
Material content		100% PES - Polyester staple fibers			
Stitching yarn		100 % PES			
Colour		White			
<b>DIMENSION, PACKAGING AND STORAGE</b>					
Roll width [ $\pm 4\%$ ]	m	90 - 180 cm			
Roll length	m	35			
Packaging		Rolls are packed in PE foil, and wind up without paper tubes			
Storage		In covered, clean and dry spaces			

The above technical parameters are average values and serve for general information. The manufacturer reserves the right to change it.

