



SINCE
1950

MALERVLIES

Nonwoven needle punched textile



PG035 217574
OETI



Characteristic: Nonwoven textile mechanically bonded by needle punching and laminated by anti-slip transparent PE foil

Material content: 100 % Recycled fibres
PE foil, transparent, anti-slip, 20 - 25 g/m²
EVA binder

Color: Multicolor

Weight: 200 to 300 g/m²

Standard width: 1 or 2 m

Function:



PROTECTION



SEPARATION



ANTI-SLIP

Use:



Material specification sheet

Date: 25. 11.2025



TRADITIONAL QUALITY NONWOVENS

Material specification sheet

Date: 25. 11.2025

MALERVLIES

Nonwoven needle punched textile

MALERVLIJS		230	250	270	300
PHYSICAL PROPERTIES					
Weight [±10 %] / EN 29073-1	g/m²	230	250	270	300
Thickness / DIN 53855-3	mm	1,4	1,6	1,7	1,8
FUNCTION					
ANTI-SLIP		X	X	X	X
Protection	P	X	X	X	X
CHARACTERISTICS					
Description		Nonwoven textile mechanically bonded by needle punching and laminated by transparent anti-slip PE foil			
Material content		Recycled fibres			
		PE foil, transparent, anti-slip, 20 - 25 g/m2			
		EVA binder			
Color		Various			
DIMENSION, PACKAGING AND STORAGE					
Roll width	m	1 or 2	1 or 2	1 or 2	1 or 2
Roll length	m	10, 25 or 50	25 or 50	25 or 50	25 or 50
Packaging		Rolls are packed in PE foil.			
Storage		In covered, clean and dry spaces			

The above technical parameters are average values and serve for general information. The manufacturer reserves the right to change it.