



SINCE
1950

TRADITIONAL QUALITY NONWOVENS

RONVAT

Filling and thermal insulating fibrous layer with
cover textile



PG035 217550
OETI



- Characteristics:** Stitched-bonded fibrous layer with cover textile
- Material content:** 100 % PES staple fibers
Stitching cotton yarn
Spunbond PP or PES
- Color:** White
- Weight:** From 150 to 300 g/m²
- Maximum width:** 200 cm
- Regular use:** Filling and thermal insulating fibrous layer



Material specification sheet

Date: 25. 11. 2025



SINCE
1950

TRADITIONAL QUALITY NONWOVENS

Material specification sheet

Date: 25. 11. 2025

RONVAT

Filling and thermal insulating fibrous layer with
cover textile

RONVAT		220	230
PHYSICAL PROPERTIES			
Weight [±10 %] / ČSN EN 12 127	g/m ²	220	230
CONSTRUCTION			
Spacing between stitches [±5 %]	cm	8,0	
MECHANICAL PROPERTIES			
Description		Nonwoven textile (fibrous layer) mechanically bonded by stitching yarn	
Material content	Fibrous layer	100% PES - Polyester staple fibers	
	Cover textile	Spunbond PP or PES / 17 or 25 g/m ²	
	Stitching yarn	100 % cotton	
Color		White	
DIMENSIONS, PACKAGING AND STORAGE			
Width [±4 %]	cm	200	
Lenght	m	30 / 35	
Packaging		The rolls are wound without a paper tube and wrapped in PE foil. Possibility of vacuuming.	
MOQ		1000 m ²	
Storage		In covered, clean and dry spaces	

The above technical parameters are average values and serve for general information. The manufacturer reserves the right to change it.