



TRADITIONAL QUALITY NONWOVENS

SORPTION CARPET
Nonwoven needle punched textile



STANDARD 100 PG035 217550 OETI



Characteristic: Nonwoven textile mechanically bonded by needle punching and laminated by transparent PE foil

Material content: 100 % Polypropylene staple fibers
PE foil, transparent, anti-slip, 20 - 25 g/m²*
EVA binder*

Color: Multicolor

Function: Sorption and trapping of drips, surface leakage of oil, lubricant or water. Anti-slip finish.



OIL AND FATS
SORPTION



ANTI-SLIP

Use: Prevention of floor contamination



* Only for sorption carpet type PE

Material specification sheet

Date: 25. 11. 2025



SINCE
1950

TRADITIONAL QUALITY NONWOVENS

Material specification sheet

Date: 25. 11. 2025

SORPTION CARPET

Nonwoven needle punched textile

	SORPTION CARPET	M	PE	
PHYSICAL PROPERTIES				
Weight / EN ISO 9864	g/m ²	250	300	± 10 %
Thickness 0,1 kPa / EN ISO 9073-2	mm	1,7	2	± 10 %
DIMENSIONS		roll	roll	
Delivered format				
Width	cm	91	91	± 1 cm
length	m	30 or 45	31 or 45	
CHARACTERISTICS				
Description	Nonwoven textile mechanically bonded by needle punching and laminated by transperated anti-slip PE foil			
Material content		100% PP staple fibers	100% PP staple fibres	
		PE anit-slip foil		
		EVA powder		
Surface finish of the reverse side		melting	PE anti-slip foil	
Color		multicolour	multicolour	
PACKAGING AND STORAGE				
Packaging	Rolls are packed in PE foil.			
Storage	In covered, clean and dry spaces			

The above technical parameters are average values and serve for general information. The manufacturer reserves the right to change it.