



21

## DECLARATION OF CHARACTERISTICS

Number: **MK HQ PES K 500 / 2021**

Polyester needlepunched calendered nonwoven geotextile Mokrutex HQ PES K

1. **MOKRUTEX HQ PES K 500**

2. Needle punched nonwoven geotextile used for building of motorways, railways, land buildings, bulding of dams, canals and drainage systems with separation and filtration, protection, drainage function (S, F, P, D)

3. RETEX a.s.  
U nádraží 894  
672 01 Moravský Krumlov, CZ  
e: geo@retex.cz · i: www.retex.cz

4. ...

5. System for adjudication and verification of building products : **2+**

6.a Textilní zkušební ústav s.p. - notified subjekt 1021 executed initial adjudication of production management system in accordance with system 2 +, performs regular witness on the production system and issued certificate No. 1021-CPR - 100 - 1/17

Character	Norm	Unit	Mean value	Tolerance	Harmonic technic norm
Square weight	EN ISO 9864	g/m <sup>2</sup>	500	± 10 %	EN 13249:2016
Strength	MD	kN/m	21	-2	EN 13250:2016
	CMD	kN/m	21	-2	EN 13251:2016
Tensibility	MD	%	80	± 20	EN 13252:2016
	CMD	%	90	± 20	EN 13253:2016
Thickness 2 kPa	EN ISO 9863-1	mm	2,1	± 15 %	EN 13254:2016
Static puncture - CBR test	EN ISO 12236	kN	3,1	-0,2	EN 13255:2016
Dynamic puncture - cone drop test	EN ISO 13433	mm	9	+1	EN 13256:2016
Determination of the pyramid puncture resistance	EN 14574	N	349	-20	EN 13257:2016
Characteristic opening size O <sub>90</sub>	EN ISO 12956	µm	61	± 15	EN 13265:2016
Water permeability vertically to the plane V <sub>I,ISO</sub>	EN ISO 11058	l/m <sup>2</sup> . s	2,46	-1.2	
Determination of water flow capacity in their plane - gradient 0.1 / longitudinal direction	20 kPa	EN ISO 12958	l/m.s	± 15 %	
	100 kPa				
	200 kPa				
Determination of water flow capacity in their plane - gradient 0.1 / longitudinal direction	20 kPa	EN ISO 12958	l/m.s	± 15 %	
	100 kPa				
	200 kPa				
Resistance to weather conditions	EN ISO 12224	Must be covered within 2 weeks after being placed			
Determining the resistance to hydrolysis (durability)	MD	EN ISO 13438	88,40%		-
	CMD		110,90%		
Long term protection efficiency 300 kPa	EN 13719	%	1,39	± 10%	
Dangerous substances		Less than EU states requirements			Valid national regulations EU states

It is assumed that nonwoven will be durable for a minimum of 25 years in natural soils with 4<pH<9 with soil temperature < 25 °C.

8. ...

Characteristics of the above mentioned product are in accordance with complex of declared characteristics.  
This declaration of characteristics is in accordance with EU directive No. 305/2011 issued in responsibility of producer mentioned above.

Signed by the manufacturer and his name:  
In Moravský Krumlov : 21.12.2021

Ing. Robert Šimek, Ph.D.  
Chairman of the executive board